



SAFETY DATA SHEET

SDS # : 089906

HI-PERF 4T 300 SAE 40

Issuing date: 2019-10-11

Revision Date: 2019-11-06

Version 1.01

1. IDENTIFICATION OF THE SUBSTANCE/MIXTURE AND OF THE COMPANY/UNDERTAKING

1.1. Product identifier

Product name	HI-PERF 4T 300 SAE 40
Number	O7A
Substance/mixture	Mixture

1.2. Relevant identified uses of the substance or mixture and uses advised against

Identified uses	Automotive (motor) oil, 4-stroke.
------------------------	-----------------------------------

1.3. Details of the supplier of the safety data sheet

Supplier	TOTAL OIL ASIA PACIFIC PTE LTD 182 Cecil Street #27-01 Frasers Tower Singapore 069547 Tel: +65 6879 2200 Fax: +65 6879 2203
	See section 16 for additional information

For further information, please contact:

Contact Point	HSE
E-mail Address	ms.ap-sds@total.com

1.4. Emergency telephone number

Asia-Pacific: +65 3158 1074
Philippines: +65 3158 1203

2. HAZARDS IDENTIFICATION

Classification of the substance or mixture

Classification
Not Classified

Label elements

Signal word	None
--------------------	------

Hazard Statements
None



SAFETY DATA SHEET

SDS # : 089906

HI-PERF 4T 300 SAE 40

Issuing date: 2019-10-11

Revision Date: 2019-11-06

Version 1.01

Other hazards which do not result in classification

Physical-Chemical Properties Contaminated surfaces will be extremely slippery.

Environmental properties The product may form an oil film on the water surface that may stop the oxygen exchange.

3. COMPOSITION/INFORMATION ON INGREDIENTS

Does not contain hazardous substances above regulatory disclosure thresholds

Chemical nature Mineral oil of petroleum origin

Additional information Product containing mineral oil with less than 3% DMSO extract as measured by IP 346

4. FIRST AID MEASURES

4.1. Description of first-aid measures

General advice	IN CASE OF SERIOUS OR PERSISTENT CONDITIONS, CALL A DOCTOR OR EMERGENCY MEDICAL CARE.
Eye contact	Immediately flush with plenty of water. After initial flushing, remove any contact lenses and continue flushing for at least 15 minutes. Keep eye wide open while rinsing.
Skin contact	Wash off immediately with soap and plenty of water while removing all contaminated clothes and shoes. Wash contaminated clothing before reuse.
Inhalation	Remove casualty to fresh air and keep at rest in a position comfortable for breathing. If not breathing, give artificial respiration.
Ingestion	Clean mouth with water. Do NOT induce vomiting. Never give anything by mouth to an unconscious person. Call a physician or Poison Control Center immediately.
Protection of First-aiders	First aider needs to protect himself. See Section 8 for more detail. Do not use mouth-to-mouth method if victim ingested or inhaled the substance; induce artificial respiration with the aid of a pocket mask equipped with a one-way valve or other proper respiratory medical device.

4.2. Most important symptoms and effects, both acute and delayed

Skin contact Not classified based on available data.

Eye contact Not classified based on available data.



SAFETY DATA SHEET

SDS # : 089906

HI-PERF 4T 300 SAE 40

Issuing date: 2019-10-11

Revision Date: 2019-11-06

Version 1.01

Inhalation Not classified based on available data. Inhalation of vapors in high concentration may cause irritation of respiratory system.

Ingestion Not classified based on available data. Ingestion may cause gastrointestinal irritation, nausea, vomiting and diarrhea.

4.3. Indication of any immediate medical attention and special treatment needed

Notes to physician Treat symptomatically.

5. FIRE-FIGHTING MEASURES

5.1. Extinguishing media

Suitable Extinguishing Media Carbon dioxide (CO₂). ABC powder. Foam. Water spray or fog.

Unsuitable Extinguishing Media Do not use a solid water stream as it may scatter and spread fire.

5.2. Special hazards arising from the substance or mixture

Special Hazard Incomplete combustion and thermolysis may produce gases of varying toxicity such as carbon monoxide, carbon dioxide, various hydrocarbons, aldehydes and soot. These may be highly dangerous if inhaled in confined spaces or at high concentration. Combustion products include sulphur oxides (SO₂ and SO₃) and Hydrogen sulphide H₂S, Mercaptans, Nitrogen oxides (NO_x), Phosphorous oxides, Zinc oxides.

5.3. Advice for fire-fighters

Special protective equipment for fire-fighters Wear self-contained breathing apparatus and protective suit.

Other information Cool containers / tanks with water spray. Fire residues and contaminated fire extinguishing water must be disposed of in accordance with local regulations.

6. ACCIDENTAL RELEASE MEASURES

6.1. Personal precautions, protective equipment and emergency procedures

General Information Do not touch or walk through spilled material. Contaminated surfaces will be extremely slippery. Use personal protective equipment. Ensure adequate ventilation. Remove all sources of ignition.

6.2. Environmental precautions

General Information Do not allow material to contaminate ground water system. Prevent entry into waterways, sewers, basements or confined areas. Local authorities should be advised if significant spillages cannot be contained.



SAFETY DATA SHEET

SDS # : 089906

HI-PERF 4T 300 SAE 40

Issuing date: 2019-10-11

Revision Date: 2019-11-06

Version 1.01

6.3. Methods and material for containment and cleaning up

Methods for containment	Dike to collect large liquid spills. If necessary dike the product with dry earth, sand or similar non-combustible materials.
Methods for cleaning up	Dispose of contents/container in accordance with local regulation. In case of soil contamination, remove contaminated soil for remediation or disposal, in accordance with local regulations.

6.4. Reference to other sections

Personal Protective Equipment	See Section 8 for more detail.
Waste treatment	See section 13.

7. HANDLING AND STORAGE

7.1. Precautions for safe handling

Advice on safe handling	For personal protection see section 8. Use only in well-ventilated areas. Do not breathe vapors or spray mist. Avoid contact with skin, eyes and clothing.
Prevention of fire and explosion	Take precautionary measures against static discharges.
Hygiene measures	Ensure the application of strict rules of hygiene by the personnel exposed to the risk of contact with the product. When using, do not eat, drink or smoke. Wash hands before breaks and immediately after handling the product. Regular cleaning of equipment, work area and clothing is recommended. Do not use abrasives, solvents or fuels. Do not dry hands with rags that have been contaminated with product. Do not put product contaminated rags into workwear pockets.

7.2. Conditions for safe storage, including any incompatibilities

Technical measures/Storage conditions	Keep away from food, drink and animal feedingstuffs. Keep in a banded area. Keep container tightly closed. Keep preferably in the original container. Otherwise reproduce all indication of the regulation label on the new container. Do not remove the hazard labels of the containers (even if they are empty). Design the installations in order to avoid accidental emissions of product (due to seal breakage, for example) onto hot casings or electrical contacts. Store at room temperature. Protect from moisture.
Materials to Avoid	Strong oxidizing agents.

8. EXPOSURE CONTROLS/PERSONAL PROTECTION

8.1. Control parameters

Exposure limits	Mineral oil mist:
------------------------	-------------------



SAFETY DATA SHEET

SDS # : 089906

HI-PERF 4T 300 SAE 40

Issuing date: 2019-10-11

Revision Date: 2019-11-06

Version 1.01

USA: OSHA (PEL) TWA 5 mg/m³, NIOSH (REL) TWA 5 mg/m³, STEL 10 mg/m³, ACGIH (TLV) TWA 5 mg/m³ (highly refined).

Legend See section 16

8.2. Exposure controls

Appropriate engineering controls

Engineering Measures

Apply technical measures to comply with the occupational exposure limits. Ensure adequate ventilation, especially in confined areas. When working in confined spaces (tanks, containers, etc.), ensure that there is a supply of air suitable for breathing and wear the recommended equipment.

Personal Protective Equipment

General Information

Protective engineering solutions should be implemented and in use before personal protective equipment is considered. The personal protective equipment (PPE) recommendations apply to the product ITSELF. In case of mixtures or formulations, it is suggested that you contact the relevant PPE suppliers.

Respiratory protection

None under normal use conditions. When workers are facing concentrations above the exposure limit they must use appropriate certified respirators. Respirator with combination filter for vapour/particulate (EN 14387): Type A/P1. Warning ! filters have a limited use duration. The use of breathing apparatus must comply strictly with the manufacturer's instructions and the regulations governing their choices and uses.

Eye Protection

If splashes are likely to occur, wear: Safety glasses with side-shields. EN 166.

Skin and body protection

Wear suitable protective clothing. Protective shoes or boots. Long sleeved clothing. Type 4/6.

Hand Protection

Hydrocarbon-proof gloves: Fluorinated rubber, Nitrile rubber. In case of prolonged contact with the product, it is recommended to wear gloves complying with EN 420 and EN 374 standards, protecting at least for 480 minutes and having a thickness of 0,38 mm at least. These values are indicative only. The level of protection is provided by the material of the glove, its technical characteristics, its resistance to the chemicals to be handled, the appropriateness of its use and its replacement frequency. Please observe the instructions regarding permeability and breakthrough time which are provided by the supplier of the gloves. Also take into consideration the specific local conditions under which the product is used, such as the danger of cuts, abrasion, and the contact time.



SAFETY DATA SHEET

SDS # : 089906

HI-PERF 4T 300 SAE 40

Issuing date: 2019-10-11

Revision Date: 2019-11-06

Version 1.01

Environmental exposure controls

General Information The product should not be allowed to enter drains, water courses or the soil.

9. PHYSICAL AND CHEMICAL PROPERTIES

General Information

Appearance	limpid
Color	yellow To amber
Physical State @20°C	liquid
Odor	Characteristic
Odor Threshold	No information available

Important health safety and environmental information

<u>Property</u>	<u>Values</u>	<u>Remarks</u>	<u>Method</u>
pH		Not applicable	
Melting point/range		Not applicable	
Boiling point/boiling range		No information available	
Flash point	246 °C 475 °F		ASTM D 92 ASTM D 92.
Evaporation rate		No information available	
Flammability Limits in Air			
upper		No information available	
Lower		No information available	
Vapor Pressure		No information available	
Vapor density		No information available	
Relative density	0.881	@ 15 °C	ASTM D 4052
Density	881 kg/m ³	@ 15 °C	ASTM D 4052
Water solubility		Insoluble	
Solubility in other solvents		No information available	
logPow		No information available	
Autoignition temperature		No information available	
Decomposition temperature		No information available	
Viscosity, kinematic	122.8 mm ² /s	@ 40 °C	ASTM D 445
Explosive properties	Not explosive		
Oxidizing Properties	Not applicable		
Possibility of hazardous reactions	None under normal processing		

Other information



SAFETY DATA SHEET

SDS # : 089906

HI-PERF 4T 300 SAE 40

Issuing date: 2019-10-11

Revision Date: 2019-11-06

Version 1.01

Freezing Point

No information available

10. STABILITY AND REACTIVITY

10.1. Reactivity

General Information None under normal processing.

10.2. Chemical stability

Stability Stable under recommended storage conditions.

10.3. Possibility of hazardous reactions

Hazardous Reactions No dangerous reaction known under conditions of normal use.

10.4. Conditions to avoid

Conditions to avoid Keep away from open flames, hot surfaces and sources of ignition. Keep away from heat and sparks.

10.5. Incompatible materials

Materials to Avoid Strong oxidizing agents.

10.6. Hazardous Decomposition Products

Hazardous Decomposition Products Incomplete combustion and thermolysis may produce gases of varying toxicity such as carbon monoxide, carbon dioxide, various hydrocarbons, aldehydes and soot. Combustion products include sulphur oxides (SO₂ and SO₃) and Hydrogen sulphide H₂S, Mercaptans, Nitrogen oxides (NO_x), Phosphorous oxides, Zinc oxides.

11. TOXICOLOGICAL INFORMATION

11.1. Information on toxicological effects

Information on likely routes of exposure

Inhalation Not classified based on available data. Inhalation of vapors in high concentration may cause irritation of respiratory system.

Ingestion Not classified based on available data. Ingestion may cause gastrointestinal irritation, nausea, vomiting and diarrhea.



SAFETY DATA SHEET

SDS # : 089906

HI-PERF 4T 300 SAE 40

Issuing date: 2019-10-11

Revision Date: 2019-11-06

Version 1.01

Skin contact Not classified based on available data.

Eye contact Not classified based on available data.

Symptoms related to the physical, chemical and toxicological characteristics

Symptoms No information available.

Delayed and immediate effects as well as chronic effects from short and long-term exposure

Acute toxicity - Product Information

Oral Not classified based on available data.

Dermal Not classified based on available data.

Inhalation Not classified based on available data.

Acute toxicity - Component Information

No information available

Skin corrosion/irritation Not classified based on available data.

Serious eye damage/eye irritation Not classified based on available data.

Sensitization Not classified based on available data.

Germ Cell Mutagenicity Not classified based on available data.

Carcinogenicity Not classified based on available data. During use in engines, contamination of oil with low levels of combustion products occurs. Used motor oils have been shown to cause skin cancer in mice following repeated application and continuous exposure. Brief or intermittent skin contact with used motor oil is not expected to have serious effects in humans if the oil is thoroughly removed by washing with soap and water.

Reproductive toxicity Not classified based on available data.

Target Organ Effects (STOT) None known.

STOT - single exposure Not classified based on available data.

STOT - repeated exposure Not classified based on available data.



SAFETY DATA SHEET

SDS # : 089906

HI-PERF 4T 300 SAE 40

Issuing date: 2019-10-11

Revision Date: 2019-11-06

Version 1.01

Aspiration hazard

Not classified based on available data.

Other adverse effects

Characteristic skin lesions (pimples) may develop following prolonged and repeated exposures (contact with contaminated clothing).

12. ECOLOGICAL INFORMATION

12.1. Toxicity

Not classified based on available data.

Acute aquatic toxicity - Product Information

No information available.

Acute aquatic toxicity - Component Information

No information available.

Chronic aquatic toxicity - Product Information

No information available.

Chronic aquatic toxicity - Component Information

No information available.

Effects on terrestrial organisms

No information available.

12.2. Persistence and degradability

General Information

No information available.

12.3. Bioaccumulative potential

Product Information

No information available.

logPow

No information available

Component Information

No information available.

12.4. Mobility in soil



SAFETY DATA SHEET

SDS # : 089906

HI-PERF 4T 300 SAE 40

Issuing date: 2019-10-11

Revision Date: 2019-11-06

Version 1.01

Soil	Given its physical and chemical characteristics, the product generally shows low soil mobility.
Air	Loss by evaporation is limited.
Water	The product is insoluble and floats on water.

12.5. Results of PBT and vPvB assessment

PBT and vPvB assessment No information available.

12.6. Other adverse effects

General Information No information available.

13. DISPOSAL CONSIDERATIONS

13.1. Waste treatment methods

Waste Disposal Methods	Should not be released into the environment. Do not empty into drains. Dispose of in accordance with all applicable national environmental laws and regulations. Where possible recycling is preferred to disposal or incineration.
Contaminated packaging	Empty containers should be taken to an approved waste handling site for recycling or disposal.
Disposal Precautions	Refer to section 8 for safety and protective measures for disposal personnel.

14. TRANSPORT INFORMATION

<u>ADR/RID</u>	Not regulated
<u>IMDG/IMO</u>	Not regulated
<u>ICAO/IATA</u>	Not regulated

15. REGULATORY INFORMATION

<u>International Inventories</u>	All the substances contained in this product are listed or exempted from listing in the following inventories: Philippines (PICCS) Canada (DSL/NDSL)
---	--



SAFETY DATA SHEET

SDS # : 089906

HI-PERF 4T 300 SAE 40

Issuing date: 2019-10-11

Revision Date: 2019-11-06

Version 1.01

Australia (AICS)
Japan (ENCS)
U.S.A. (TSCA)
Korea (KECL)
Taiwan (TCSI)

National regulatory information

Singapore

This Safety Data Sheet (SDS) has been prepared according to Singapore Standard SS 586 on "Specification for Hazard Communication for Hazardous Chemicals and Dangerous Goods"

Applicable National Regulation:
Workplace Safety and Health (General Provision) Regulations

Philippines

This Safety Data Sheet (SDS) has been prepared according to EMB Memorandum Circular on "Guidance Manual for Department Administrative Order 2015-09, Rules and Procedures for the Implementation of GHS in Preparation of SDS and Labelling Requirements of Toxic Chemical Substances"

Priority Chemical List

Not regulated

Chemical Control Order

Not regulated

16. OTHER INFORMATION

Abbreviations, acronyms

ACGIH = American Conference of Governmental Industrial Hygienists

bw = body weight

bw/day = body weight/day

EC x = Effect Concentration associated with x% response

GLP = Good Laboratory Practice

IARC = International Agency for Research of Cancer

LC50 = 50% Lethal concentration - Concentration of a chemical in air or a chemical in water which causes the death of 50% (one half) of a group of test animals

LD50 = 50% Lethal Dose - Chemical amount, given at once, which causes the death of 50% (one half) of a group of test animals

LL = Lethal Loading

NIOSH = National Institute of Occupational Safety and Health

NOAEL = No Observed Adverse Effect Level

NOEC = No Observed Effect Concentration

NOEL = No Observed Effect Level

OECD = Organization for Economic Co-operation and Development

OSHA = Occupational Safety and Health Administration

UVCB = Substance of unknown or Variable composition, Complex reaction products or Biological material



SAFETY DATA SHEET

SDS # : 089906

HI-PERF 4T 300 SAE 40

Issuing date: 2019-10-11

Revision Date: 2019-11-06

Version 1.01

Legend Section 8

OEL = Occupational Exposure Limit

TWA: Time Weight Average

STEL: Short Time Exposure Limit

PEL: Permissible exposure limit

REL: Recommended exposure limit

TLV: Threshold Limit Values

+ Sensitizer

** Hazard Designation

M: Mutagen

*

C:

R:

Skin designation

Carcinogen

Toxic to reproduction

Revision Date: 2019-11-06

Revision Note *** Indicates updated section.

Additional details on the supplier of the product

PHILIPPINES Supplier

Total (Philippines) Corporation
 7th Floor, 11th Corporate Center
 11th Avenue, corner Triangle Drive,
 North Bonifacio, Bonifacio Global City
 1634 Taguig City
 Philippines
 Tel : +63 2 8490888
 Fax : +63 2 8490889

This safety data sheet serves to complete but not to replace the technical product sheets. The information contained herein is given in good faith and is accurate to the best of knowledge at the date indicated above. It is understood by the user that any use of the product for purposes other than those for which it was designed entails potential risk. The information given herein in no way dispenses the user from knowing and applying all provisions regulating his activity. The user bears sole liability for the precautions required when using the product. The regulatory texts indicated herein are intended to aid the user to fulfil his obligations. This list is not to be considered complete and exhaustive. It is the user's responsibility to ensure that he is subject to no other obligations than those mentioned.

End of the Safety Data Sheet