

# TOTAL HI-PERF 4T 300 SAE 40

4-Stroke Engine Oil

## KEY DATA

### MOTORCYCLE RANGE

MINERAL ENGINE OIL



### INTERNATIONAL STANDARDS

- API SF

## APPLICATIONS

**TOTAL HI-PERF 4T 300 SAE 40** is a quality 4-stroke engine oil for motorcycles which provides great lubrication and protection to all vital parts of the engine. This results in trouble-free performance of the engine between recommended drain intervals.

## CHARACTERISTICS

TEST	UNIT	TEST METHOD	RESULT
Viscosity grade	-	SAE J300	SAE 40
Kinematic viscosity at 40°C	mm <sup>2</sup> /s	ASTM D445	127.2
Kinematic viscosity at 100°C	mm <sup>2</sup> /s	ASTM D445	13.2
Viscosity Index	-	ASTM D2270	97
Flashpoint	°C	ASTM D92	280
Pour point	°C	ASTM D97	-21
Density	Kg/m <sup>3</sup>	ASTM D1298	895

## RECOMMENDATIONS FOR USE

Before using the product, the vehicle's maintenance guide should be checked. Oil changes should be carried out in accordance with the manufacturer's recommendations.

The product should not be stored at temperatures over 60°C. It should be kept away from sunlight, intense cold and extreme temperature fluctuations.

If possible, the packaging should not be exposed to the elements. Otherwise, the drums should be laid horizontally in order to avoid any contamination from water and to prevent the product's label from rubbing off.

## HEALTH, SAFETY AND THE ENVIRONMENT

Based on the toxicological information available, this product should not cause any adverse health effects, provided it is used for its intended purpose and in accordance with the recommendations laid out in the Safety Data Sheet. This can be obtained on request from your local reseller and is available for consultation at [www.quickfds.fr](http://www.quickfds.fr).

This product should not be used for any purposes other than the ones for which it is intended.