

TOTAL HI-PERF 4T 900 10W-50

4-Stroke Engine Oil

KEY DATA

MOTORCYCLE RANGE

SYNTHETIC ENGINE OIL

JASO MA2 - M033TOL162

INTERNATIONAL STANDARDS

API SN









TECHNOLOGY

Durability Improver technology

4 Actions to maximize the durability of your bike:

- Protection against harmful piston deposits
- Protection against gear pitting and wear
- Protection against clutch slippage
- Protection against thermo-oxidative attack



APPLICATIONS

TOTAL HI-PERF 4T 900 10W-50 is a fully synthetic 4-stroke engine oil specially designed for all types of motorcycles including racing bikes. Formulated with Durability Improver technology, it brings ultimate performance under all temperatures and improved power and acceleration whether on the road or on the race track.

CHARACTERISTICS

TEST	UNIT	TEST METHOD	RESULT
Viscosity grade	-	SAE J300	10W-50
Kinematic viscosity at 40°C	mm²/s	ASTM D445	119,4
Kinematic viscosity at 100°C	mm²/s	ASTM D445	17,7
Viscosity Index	-	ASTM D2270	164
Flashpoint	°C	ASTM D92	250
Pour point	°C	ASTM D97	-36
Density	Kg/m ³	ASTM D1298	853,4

RECOMMENDATIONS FOR USE

Before using the product, the vehicle's maintenance guide should be checked. Oil changes should be carried out in accordance with the manufacturer's recommendations.

The product should not be stored at temperatures over 60°C. It should be kept away from sunlight, intense cold and extreme temperature fluctuations.

If possible, the packaging should not be exposed to the elements. Otherwise, the drums should be laid horizontally in order to avoid any contamination from water and to prevent the product's label from rubbing off.

HEALTH, SAFETY AND THE ENVIRONMENT

Based on the toxicological information available, this product should not cause any adverse health effects, provided it is used for its intended purpose and in accordance with the recommendations laid out in the Safety Data Sheet. This can be obtained on request from your local reseller and is available for consultation at www.quickfds.fr.

This product should not be used for any purposes other than the ones for which it is intended.

TOTAL LUBRIFIANTS – Immeuble Spazio 562, avenue du Parc de l'île 92029 Nanterre cedex France TOTAL HI-PERF 4T 900 10W-50 Last update of this datasheet: 03/2020